

Core Alignment Fusion Splicer

**Touch Screen
+ Button**



Automatic Fiber Identification

Smart ARC calibration

**Windproof, Waterproof IPX2
Dustproof IP5X, Anti-shock**

**G.654E fiber splice mode for
5G Network**

6 Sec. Splicing , 12 Sec. Heating

Password Anti-theft

Integrated GPU processor

**Long life battery, more than
420 times splice and heat cycles**



Package



01	Carrying case	02	Fusion splicer X6+
03	Large capacity battery BAT-01	04	Adapter
05	High precision cleaver JF-50	06	Alcohol bottle
07	Extra electrodes JE-03	08	Cooling tray
09	Stripper CFS-05	10	Drop cable stripper
11	Shoulder strap	12	USB Cable JU-01
13	Hand strap		



Standard Package

Size&Weight	D156×W140×H150(mm),2.0kg(2.5kg with battery)
Motors No.	High precision 6 motors
Fiber alignment	Core to core alignment
Holder type	Multi-functional fiber holder,compatible for bare fiber,drop cable,patch cord
Applicable fibers	SM(ITU-T G.652),EB(ITU-TG.654),MM(ITU-TG.651),DS(ITU-TG.653),NZ/NZDS(ITU-TG.655),BI(ITU-TG.657)
Fiber diameter	Cladding 80~150μm, coating 100~3000μm
Cleave length	5~16mm
Splice mode	Max.200
Splice time	6 sec. [SM Fast] program, 10 sec. [SM G. 652] program
Heating mode	Max.30
Heating time	Adjustable, 8 sec. with micro sleeves, 12 sec. with slim 60 mm and 40mm sleeves
Splice protector	10~60mm
Splice image capture	Max.800
Splice data storage	Max.20000
Splice loss	SM:0.01dB, EB:0.02dB, MM:0.01dB, DS:0.02dB, NZ/NZDS:0.02dB, BI:0.02dB
Return loss	>>60dB
Loss estimation	Provided
Operation condition	Altitude 0~5000m, Humidity 0~95%, Temperature -20~+50°C, Wind velocity up to 15m/s
Storage condition	Humidity 0~95%, Temperature -40~+80°C, (Battery -20~+40°C)
Tension	1.96~2.25N
Screen	4. 3 inch high-light color touch screen
Magnification	400x for X&Y dual axis view, 800x for X or Y single axis view(zoom up)
Electrode life	5000 splices
Power supply	AC100-240V , 50/60Hz
Battery capacity	8400 mAh High capacity battery, more than 450 times splicing and heating