



OPZ/JJ-JCL Series Fiber Optic Terminal Box



OPZ/JJ-JCL

Introduction

OPZ/JJ-JCL series optical fiber terminal box can be applied in the branch connection of fiber termination, working as distribution box, 19" standard structure, rack mounting, available for the installation of FC, SC, ST, LC adaptors.

Structural features

- All property indexes are in accordance with National YD/T925—1997 Standard.
- The body make use of cold rolling steel sheet Strong adhesive force, artistic and durable.
- Distinctive design of 1-2 cable entrance and fiber exit of 1-24 cores assures flexibility.
- Cable entrance are sealed with oil resistance NBR to increase the flexibility. Users can choose to prick the entrance and exit.
- Overlapping fiber-melting tray and separate insulation earth unit make the disposition of the cores, expanding the capacity and cable-earthen flexible, convenient and safe.

Technical specifications

- External Size: (length×width×height) 430x250x1U/2U
- optical fiber winding radius: $\geq 40\text{mm}$
- extra loss of fiber tray: none
- fiber length left in tray: $\geq 1.6\text{m}$
- fiber capacity: 48 cores
- working temperature: $- 40^{\circ}\text{C} \sim + 60^{\circ}\text{C}$
- lateral pressure-resistance: 500N
- shock-resistance: 750N



Order Guide

Type	Dimension(mm)	Max capacity cores	Remark
OPZ/JJ-JCL24	480*250*1U	24	available for FC,ST,SC,LC .
OPZ/JJ-JCL48	480*250*2U	48	
OPZ/JJ-JCL72	480*250*3U	72	
OPZ/JJ-JCL96	480*250*4U	96	
OPZ/JJ-JCL144	480*250*6U	144	

Packing information

Type	Inner carton dimension/ weight	Outside carton dimension/weight	No./carton
OPZ/JJ-JCL24	465*285*75mm / 2.6kg	485*425*305 / 14.2kg	5
OPZ/JJ-JCL48	465*285*125mm / 3.8kg	675*485*305 / 21kg	
OPZ/JJ-JCL72			3
OPZ/JJ-JCL96			2
OPZ/JJ-JCL144			2